163. The microfluidic reactor according to claim 162, wherein the reaction cells are adapted for use of in situ generated chemical reagents which are generated in solution in the illumination chamber.

II. <u>REMARKS</u>

The above amendments have been made to focus the claims of the present application, and to clarify the pending claims. The additional claims 160-163 do not add new matter to the application and their entry is therefore respectfully requested.

IV. **CONCLUSION**

In light of the foregoing amendments and remarks, Applicants respectfully submit that

the present application and all claims are in condition for immediate allowance and early notice

to such effect is earnestly solicited. If, in the opinion of the Examiner, a phone call may help

expedite prosecution of this application, the Examiner is invited to contact the undersigned

attorney at (512) 542-8569.

Attached hereto is a marked-up version of the changes made to the claims by the current

amendments. The attached page is captioned "Version With Markings to Show Changes

Made."

Please date stamp and return the enclosed postcard evidencing receipt of these materials.

Respectfully submitted,

Margaret J. Sampson

Margaret C

Registration. No. 47,052

Attorney for Applicants

VINSON & ELKINS L.L.P.

2300 First City Tower 1001 Fannin Street

Houston, Texas 77002-6760

Ph: (512) 542-8569 Fax (512) 236-3264

Date: September 6, 2002

6

Version With Markings to Show Changes Made

A. In the Claims:

Claims 1, 7, 18, 35, 43, 46, 47, 100, 104, 145, 150, and 159 have been amended as follows:

- 1. (Amended) A microfluidic reactor comprising:
 - a plurality of flow-through reaction cells for parallel chemical reactions, each reaction cell comprising:
 - i. at least one illumination chamber, and
 - ii. at least one reaction chamber,

wherein the illumination chamber and the reaction chamber are in flow communication and are spatially separated in the reaction cell.

- 7. (Amended) A microfluidic reactor according to claim 1, wherein the reaction cells are adapted for use of in situ generated chemical reagents which are generated in solution in the illumination chamber.
- 18. (Amended) A microfluidic reactor according to claim 1, wherein the reactor further comprises an inlet channel and an inlet restriction gap connected to the illumination chamber, and an outlet channel and an outlet restriction gap connected to the illumination reaction chamber.
- 35. (Amended) A microfluidic reactor according to claim 34, wherein the fluid channels have a first cross sectional area, the reaction cells have a second cross sectional area which is smaller than the first cross sectional area, and the ratio between the first and second cross sectional areas is 10 to 10,000 from 1:10 to 1:1000.
- 43. (Amended) A microfluidic reactor according to claim 1, wherein the device comprises an array of oligonucleotides in the reaction chambers, a microfluidic template made of

silicon, <u>at least one</u> window <u>plate</u> plates, a shadow mask, inlet channels and inlet restriction gaps connected to the illumination chambers, outlet channels and outlet restriction gaps connected to the reaction chambers, distribution channels for parallel reactions in the reaction cells, and connection channels to connect illumination <u>chambers</u> and reaction chambers.

- 46. (Amended) A microfluidic reactor according to claim 43 45, wherein the oglionucleotides oligonucleotides are immobilized with use of linker molecules.
- 47. (Amended) A microfluidic reactor according to claim <u>1</u> 46, wherein the reaction cells, illumination chambers, and reaction chambers are adapted for use of in situ generated chemical reagents <u>in solution</u>.
- 100. (Amended) A microfluidic reactor comprising at least one microfluidic template and at least one window plate plates attached to the template, the microfluidic template and the window plate plates defining a plurality of reaction cells which provide for flow of liquid solution through the cells for parallel chemical reactions, each reaction cell comprising a first chamber in fluid communication with but spatially separated from a second chamber, the first chamber being adapted to be an illumination chamber, and the second chamber being adapted to be a reaction chamber for reaction of photo-generated products in the first chamber.
- 104. (Amended) A microfluidic reactor according to claim 100, wherein the first chamber is connected to an inlet channel, the second chamber is connected to an outlet channel, and the plurality of reaction cells are connected by distribution channels for parallel chemical reactions.

- 145. (Amended) A microfluidic reactor comprising a plurality of flow-throughphotoillumination reaction cells for parallel chemical reactions, each reaction cell
 comprising at least one illumination chamber and at least one reaction chamber, wherein
 the illumination chamber and the reaction chamber are in fluid communication and are
 spatially separated in the reaction cell, wherein the plurality of reaction cells are in fluid
 communication with at least one inlet channel and at least one outlet channel, wherein the
 reaction cells are connected in parallel with fluid distribution channels, wherein each
 reaction cell has a separate outlet channel which allows for individual collection of
 effluent from each reaction cell.
- 150. (Amended) A microfluidic reactor adapted for in situ use of photogenerated reagents in solution, wherein the reactor comprises an inlet channel, an illumination chamber, a connection channel, a reaction chamber, and an outlet channel, wherein the illumination chamber connects with the inlet channel, the connection channel connects the illumination chamber and the reaction chamber, and the outlet channel connects with the reaction chamber.
- 159. (Amended) A method for enhancing parallel photochemical reactivity in a microfluidic reactor having a plurality of isolated reaction cells, said method comprising the step of providing spatially separated or overlapping illumination and reaction chambers in each reaction cell.

Newly added claims:

160. The microfluidic reactor according to claim 1, wherein predetermined illumination chambers are illuminated by digital-micromirror-device-based light projection.

- 161. A chip according to claim 48, wherein the chip has a configuration with one or more levels.
- 162. A microfluidic reactor comprising:

a plurality of flow-through reaction cells, each reaction cell comprising:

- i. at least one illumination chamber, and
- ii. at least one reaction chamber,

wherein the illumination chamber and the reaction chamber are in flow communication and are spatially separated in the reaction cell; wherein digital-micromirror-device-based light projection illuminates predetermined illumination chambers.

163. The microfluidic reactor according to claim 162, wherein the reaction cells are adapted for use of in situ generated chemical reagents which are generated in solution in the illumination chamber.